

FITTING INSTRUCTION

Part Number APH40 Arcadian replacement Rollers and Spindles for Henderson Pre Premiere Canopy Doors.

WARNING As spring tension is on the door at all times great care must be taken.

All work is undertaken from within the garage therefore ensure all tools required are at hand. You may require assistance with step (1)

- 1 Ease the spring tension using a .25" dia toggle bar in the spring clamp at the left hand end of the spring then insert the tension pin in the hole on the spring shaft within the right hand door bracket, ensuring that the pin rests on the top of the bracket support. This removes the tension from the cables.
- 2 Remove the screw at the base of the side jamb channel and the screw holding the bracket half way up (if fitted), this allows removal of the cable from the old roller and spindle.
- 3 Remove the circlips from the spindle (noting their position), remove the old roller and spindle and replace with the new one fitting the circlips in the same position. (see note below).
- 4 Replace the screws in the side jamb channels
- 5 Carefully remove the tension pin and then check that the cable runs on the top groove of the cone.

NOTE: If there is insufficient room between the brickwork and the roller and spindle to remove them, remove the bottom weather strips and ease the bottom of the door into the garage. This will allow sufficient room to remove and replace the roller and spindle.

ALL WORK IS UNDERTAKEN AT THE OWNERS RISK